



Combining classic stove design with cutting-edge, high efficiency combustion systems, the all-new Huntingdon 30 Ecodesign stove brings warmth and character to vour home.

Tasteful detailing decorates each stove's cast iron door, side panels and top plate — testament to the craftsmanship behind each stove.

A single air control responds with quality you can feel, allowing you to quickly adjust the stove's airflow system for rapid start-up or easy heat output regulation.



Front cover image: Huntingdon 30 woodburning Ecodesign stove, with Tracery Door, shown with ceramic wood effect beam.

HUNTINGDON 30 ECODESIGN STOVES





Advanced burn chamber engineering and airflow technology puts the Huntingdon 30 at the forefront of stove innovation. Burning with minimal emissions, this elegant stove is suitable for urban and country homes alike, exceeding both DEFRA Smoke Control and Ecodesign air quality requirements.

The Huntingdon 30 comes in dedicated woodburning or multi-fuel versions, with either clear or tracery door options to suit your home.

KEY DETAILS

- Nominal Heat Output: 5kW Heat Output Range: 3.5 - 7.5kW
- Maximum Efficiency: 82% | Energy Class: A+
- Woodburning and Multi-fuel models
- Clear or Tracery Door options
- Ecodesign Ready
- DEFRA Smoke Control Zone exempt as standard
- Convector design lowers distances to combustibles
- Cleanburn & Airwash Systems
- Removeable door handle
- Cast iron and heavy-gauge steel construction
- Closeable grate with external riddling (multi-fuel only)
- Integrated External Air Connection
- Suitable for 12mm hearths

















计分长分长分长分长





DIMENSIONS

Product Codes

701-068	Huntingdon 30 Wood Clear Door - Black
701-473	Huntingdon 30 Multi-fuel Clear Door - Black
701-042	Huntingdon 30 Wood Tracery Door - Black
701-496	Huntingdon 30 Multi-fuel Tracery Door - Black
998-080	Outdoor Air Kit - 80mm

*Glass Viewing Area All dimensions are in mm.





	А	A1*	В	B1*	С	D	Е	F	G	Н			K	L
Huntingdon 30	552	367	602	253	520	383	602	622	670	221	130	150	128	150

DISTANCE TO COMBUSTIBLES	Distance from Sides	Distance from Rear
Huntingdon 30 Wood with twin wall flue pipe & heat shield	225mm	75mm
Huntingdon 30 Multi-fuel with twin wall flue pipe & heat shield	200mm	75mm

Note: Minimum distance to combustible material must be 450mm from any exposed single wall flue pipe



Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, England EX2 7LF

Trade Sales: 01392 474000 / NI: 01392 261990
Email: info@stovax.com / NI: northernireland@stovax.com

Export Sales: +44 1392 261990 • Email: exportsales@stovax.com

stovax.com









Find Your Local Expert Retailer





Brochure ref: H30ADD0721

